

TENDER TEXT



BOLLARDS

Zestrum

LP-BL351005



TENDER TEXT

Supply and install Zestrum (LP-BL351005) Bollard by LIGHT PLUS UK. Housing: Die-cast Aluminum with High Corrosion Resistance Powder Coated and Stainless-Steel Screws. Diffuser: Clear Pyrex Glass. Beam Angle: 15° / 36°. Color Available: White & Black. Lifespan: >100,000 Hours (L90 B50). Reflector: Aluminium Reflector. Voltage: AC100~240V. Working Temperature: -40C° ~ 55C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 66. IK: 08. Or equal and approved.

DESCRIPTION

Shielded bollards with flat beam light distribution on one side. Luminaires which illuminate the ground surfaces directly in front of their installation site with a flat beam. Their light distribution allows the luminaires to be spaced far apart and is particularly suitable for illuminating footpaths and squares. We can supply these luminaires in two sizes and in different heights for the differing dimensions of the installation site.

TECHNICAL CHARACTERISTICS

Housing	Die-cast Aluminum with High Corrosion Resistance Powder Coated and Stainless-Steel Screws.
Diffuser	Clear Pyrex Glass
Beam Angle	15° / 36°
Color Available	White & Black
Lifespan	>100,000 Hours (L90 B50)
Reflector	Aluminium Reflector
Voltage	AC100~240V

Working Temperature	-40C° ~ 55C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	66
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-BL351005	05W	LED	600lm	A90 X B128 X C700 mm
LP-BL351010	10W	LED	1200lm	A90 X B128 X C700 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.