

TENDER TEXT



BOLLARDS

Tam

LP-BL333012-H80



TENDER TEXT

Supply and install Tam (LP-BL333012-H80) Bollard by LIGHT PLUS UK. Housing: Body is Die-casting Aluminum Cover, Extruded Aluminum Pole. Finishing Surface Anti-ageing Electrostatic Spray Processing. Diffuser: PMMA. Beam Angle: 360°. Color Available: White, Black & Grey. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: 220~240V. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 66. IK: 08. Or equal and approved.

DESCRIPTION

Tam LED Light are a great design choice for gardens, walkways, and around the buildings, available with little differences in the top shape to satisfy the details lovers. The light source is an LED high efficiency system, which ensures high performances while saving energy. All the items have features like easy installation, very low maintenance needs and full safety for electrical systems and people.

TECHNICAL CHARACTERISTICS

Housing	Body is Die-casting Aluminum Cover, Extruded Aluminum Pole. Finishing Surface Anti-ageing Electrostatic Spray Processing.
Diffuser	PMMA
Beam Angle	360°
Color Available	White, Black & Grey
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	220~240V
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

IP Rating	66
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-BL333012-H80	12W	LED	1440lm	A125 X B125 X C800mm
LP-BL333015-H80	15W	LED	3000lm	A125 X B125 X C800mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.