

TENDER TEXT



BOLLARDS

Shapy

LP-BL331507-H50



TENDER TEXT

Supply and install Shapy (LP-BL331507-H50) Bollard by LIGHT PLUS UK. Housing: Die Cast Aluminium with High Corrosion Resistance Powder Coated and Stainless Steel Screws. Diffuser: High Purity Anodized Aluminium Reflector. Beam Angle: 15° / 36°. Color Available: White & Black. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: 100~240V. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 66. IK: 08. Or equal and approved.

DESCRIPTION

Shapy bollards with flat beam light distribution on one side. Luminaires which illuminate the ground surfaces directly in front of their installation site with a flat beam. Their light distribution allows the luminaires to be spaced far apart and is particularly suitable for illuminating footpaths and squares. We can supply these luminaires in two sizes and in different heights for the differing dimensions of the installation site.

TECHNICAL CHARACTERISTICS

Housing	Die Cast Aluminium with High Corrosion Resistance Powder Coated and Stainless Steel Screws
Diffuser	High Purity Anodized Aluminium Reflector
Beam Angle	15° / 36°
Color Available	White & Black
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	100~240V
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

IP Rating	66
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-BL331507-H50	07W	LED	875lm	A160 X B160 X C500mm
LP-BL331514-H100	14W	LED	1750lm	A160 X B160 X C500mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:13.