

TENDER TEXT



BOLLARDS

Orbit

LP-BL337008-H80



TENDER TEXT

Supply and install Orbit (LP-BL337008-H80) Bollard by LIGHT PLUS UK. Housing: Body is Die-casting Aluminum Cover, Extruded Aluminum Pole. Finishing Surface Anti-ageing Electrostatic Spray Processing. Diffuser: PMMA. Beam Angle: 15° / 36°. Color Available: White & Black. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: 100~240V. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 66. IK: 08. Or equal and approved.

DESCRIPTION

Orbit Bollard Light is made of die-cast aluminium EN AB – 46100, processed by means of open pore anodizing + powder coating; the diffuser is made of UV resistant polycarbonate. with ingress protection degree is IP66. The original profile is transformed into a bollard with minimal and curvy to give the landscape a pure light with low glare.

TECHNICAL CHARACTERISTICS

Housing	Body is Die-casting Aluminum Cover, Extruded Aluminum Pole. Finishing Surface Anti-ageing Electrostatic Spray Processing.
Diffuser	PMMA
Beam Angle	15° / 36°
Color Available	White & Black
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	100~240V
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

IP Rating	66
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-BL337008-H80	08W	LED	960lm	A40 X B800 mm
LP-BL337008-H60	08W	LED	960lm	A40 X B600 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:14.