

TENDER TEXT



BOLLARDS

Blurry

LP-BL338025-H80



TENDER TEXT

Supply and install Blurry (LP-BL338025-H80) Bollard by LIGHT PLUS UK. Housing: Body is Die-casting Aluminum Cover, Extruded Aluminum Pole. Finishing Surface Anti-ageing Electrostatic Spray Processing. Diffuser: PMMA. Beam Angle: 360°. Color Available: White, Gray & Black. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: 100~240V. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 66. IK: 08. Or equal and approved.

DESCRIPTION

Blurry Anti-Aged Die-cast Aluminium Head, Extruded Aluminium Body, Anodized Aluminium Louvres, PMMA Diffuser. Dattractive, vandal-resistant LED bollard designed for use in public places, parks, paths, etc. CircLED combines energy saving with indirect light distribution, which gives comfortable and pleasant lighting without light pollution. IK10. The body is made of die-cast aluminium EN AB – 46100, processed by means of open pore anodizing + powder coating; the diffuser is made of uv resistant polycarbonate. with ingress protection degree is IP66.

TECHNICAL CHARACTERISTICS

Housing	Body is Die-casting Aluminum Cover, Extruded Aluminum Pole. Finishing Surface Anti-ageing Electrostatic Spray Processing.
Diffuser	PMMA
Beam Angle	360°
Color Available	White, Gray & Black
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	100~240V

LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	66
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-BL338025-H80	25W	LED	3000lm	A168 X B800 mm
LP-BL338025-H100	25W	LED	3000lm	A168 X B800 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.