

TENDER TEXT



BOLLARDS

Stand

LP-BL331008-H40



TENDER TEXT

Supply and install Stand (LP-BL331008-H40) Bollard by LIGHT PLUS UK. Housing: Body is Die-casting Aluminum Cover, Extruded Aluminum Pole. Finishing Surface Anti-ageing Electrostatic Spray Processing. Diffuser: PMMA. Beam Angle: 90°. Color Available: Gray / Dark Gray / Black RAL7021. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC100~240V. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 66. Or equal and approved.

DESCRIPTION

Double emission bollard & pole for outdoor application. Stand LED light source with a general lighting light distribution is composed of 2 arrayed LEDs, the source luminous flux is 2600lm, nominal luminous efficacy. The device body is made of die-cast aluminium en ab – 46100 and features a grey RAL 7021 finish, processed by means of open pore anodizing + powder coating, the diffuser is made of UV resistant polycarbonate with ingress protection degree is IP66.

TECHNICAL CHARACTERISTICS

Housing	Body is Die-casting Aluminum Cover, Extruded Aluminum Pole. Finishing Surface Anti-ageing Electrostatic Spray Processing
Diffuser	PMMA
Beam Angle	90°
Color Available	Gray / Dark Gray / Black RAL7021
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC100~240V

LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	66

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-BL331008-H40	08W	LED	1040lm	A400 X B97 X C155mm
LP-BL331020 -H80	20W	LED	2600lm	A800 X B97 X C155mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.