

TENDER TEXT



DECORATIVE POLES

Vertical 50

LP-STR32701X5



TENDER TEXT

Supply and install Vertical 50 (LP-STR32701X5) Decorative Pole by LIGHT PLUS UK. Housing: Steel. Color Available: Black, Copper, Gray. Beam Angle: Symmetric / Asymmetric. Voltage: AC220~240V. Working Temperature: -25C° ~ +65C°. Operating Gear: Electronic Converter. Surge Protection: 10 kV. Mounting / Base: Buried Base 0.8m. Class: I. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 66. IK: 09. Or equal and approved.

DESCRIPTION

Transforming the aesthetics of modern street lighting, this innovative system merges functionality with minimalist design to bring a fresh sense of order to urban spaces. The streamlined structure integrates vertical optical modules into a sleek, cohesive form, delivering exceptional performance across a range of public environments. Specifically designed for versatility, the bollard and pole mounted luminaires offer ideal solutions for illuminating pathways, building perimeters, parks, and urban squares. Equipped with advanced micro-faceted reflector technology, they ensure superior visual comfort while meeting stringent glare control standards—setting a new benchmark in architectural outdoor lighting.

TECHNICAL CHARACTERISTICS

Housing	Steel
Color Available	Black, Copper, Gray
Beam Angle	Symmetric / Asymmetric
Voltage	AC220~240V
Working Temperature	-25C° ~ +65C°
Operating Gear	Electronic Converter
Surge Protection	10 kV

Mounting / Base	Buried Base 0.8m
Class	I
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	66
IK	09

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-STR32701X5	1 X 5W	LED	375lm	Ø168 X 0.8m/1m
LP-STR32702X5	2 x 5W	LED	750lm	Ø168 X 0.8m/1m/1.5m
LP-STR32703X5	3 x 5W	LED	1125lm	Ø168 X 1.5m/3m
LP-STR32706X5	6 x 5W	LED	2250lm	Ø168 X 3m/4m/6m
LP-STR32708X5	8 x 5W	LED	3000lm	Ø168 X 3m/4m/6m
LP-STR327012X5	12 x 5W	LED	4500lm	Ø168 X 3m/4m/6m

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.