

TENDER TEXT



STREET LIGHTS

Canter Bury

LP-STR321040



TENDER TEXT

Supply and install Canter Bury (LP-STR321040) Street Light by LIGHT PLUS UK. Housing: Die Cast Aluminum Body. Diffuser: Clear PC. Beam Angle: 155° / 156° / 158° / 159°. Color Available: Black & Grey. Lifespan: > 50,000 Hours (L70 B10). Voltage: AC220~240V. Working Temperature: -20C° ~ +65C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 10. Or equal and approved.

DESCRIPTION

Performance-driven LED street light for major and minor roads. Optical choices provide sharp cut-off and wide coverage where needed. Surge protection and robust sealing support dependable operation in challenging environments.

TECHNICAL CHARACTERISTICS

Housing	Die Cast Aluminum Body
Diffuser	Clear PC
Beam Angle	155° / 156° / 158° / 159°
Color Available	Black & Grey
Lifespan	> 50,000 Hours (L70 B10)
Voltage	AC220~240V
Working Temperature	-20C° ~ +65C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	65
IK	10

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-STR321040	40W	LED	4045lm	A460 X B150 X C115 mm
LP-STR321060	60W	LED	7790lm	A480 X B150 X C115 mm
LP-STR321090	90W	LED	12062lm	A530 X B170 X C115 mm
LP-STR3210120	120W	LED	15955lm	A580 X B170 X C115 mm
LP-STR3210150	40W	LED	20273lm	A630 X B170 X C115 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.