

TENDER TEXT



STREET LIGHTS

Gloucester

LP-STR320230



TENDER TEXT

Supply and install Gloucester (LP-STR320230) Street Light by LIGHT PLUS UK. Housing: Die Cast Aluminum Body. Diffuser: Clear PC. Color Available: Black & Grey. Lifespan: > 50,000 Hours (L70 B10). Voltage: AC220~240V. Working Temperature: -20C° ~ +65C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 10. Beam Angle: 48° / 120x50° / 140x30° / 150x60°. Or equal and approved.

DESCRIPTION

Performance-driven LED street light for major and minor roads. Optical choices provide sharp cut-off and wide coverage where needed. Surge protection and robust sealing support dependable operation in challenging environments.

TECHNICAL CHARACTERISTICS

Housing	Die Cast Aluminum Body
Diffuser	Clear PC
Color Available	Black & Grey
Lifespan	> 50,000 Hours (L70 B10)
Voltage	AC220~240V
Working Temperature	-20C° ~ +65C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	65
IK	10

Beam Angle	48° / 120x50° / 140x30° / 150x60°
------------	-----------------------------------

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-STR320230	30W	LED	2886lm	A503 X B233 X C66.5 mm
LP-STR320270	70W	LED	5523lm	A503 X B233 X C66.5 mm
LP-STR3202100	100W	LED	7169lm	A503 X B233 X C66.5 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.