

TENDER TEXT



DECORATIVE POLES

Inverness

LP-STR318930



TENDER TEXT

Supply and install Inverness (LP-STR318930) Decorative Pole by LIGHT PLUS UK. Housing: Extruded Aluminum Pole. Diffuser: Opal PC. Beam Angle: 110°. Color Available: Black & Grey. Lifespan: > 50,000 Hours (L70 B10). Voltage: AC220~240V. Working Temperature: -20C° ~ +65C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 10. Or equal and approved.

DESCRIPTION

Inverness LED Street light with a quiet, modern form. The sealed module achieves consistent performance in dusty or humid environments. Dimming options and controls support energy savings during low-traffic periods.

TECHNICAL CHARACTERISTICS

Housing	Extruded Aluminum Pole
Diffuser	Opal PC
Beam Angle	110°
Color Available	Black & Grey
Lifespan	> 50,000 Hours (L70 B10)
Voltage	AC220~240V
Working Temperature	-20C° ~ +65C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	65

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-STR318930	30W	LED	2717lm	A800 X B300 X C120 mm
LP-STR318940	40W	LED	3530lm	A800 X B300 X C120 mm
LP-STR318960	60W	LED	3837lm	A800 X B300 X C120 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.