

TENDER TEXT



DECORATIVE POLES

Lumen Tower

LP-STR318860



TENDER TEXT

Supply and install Lumen Tower (LP-STR318860) Decorative Pole by LIGHT PLUS UK. Housing: Die Cast Aluminum. Diffuser: Opal PC. Beam Angle: 120°. Color Available: Black & Grey. Lifespan: > 50,000 Hours (L70 B10). Voltage: AC220~240V. Working Temperature: -20C° ~ +65C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 10. Or equal and approved.

DESCRIPTION

A roadway fixture focused on visual comfort and uniformity. The flat glass and internal baffles reduce high-angle brightness, improving night-time visibility. Pre-wired terminal blocks and captive screws speed up installation.

TECHNICAL CHARACTERISTICS

Housing	Die Cast Aluminum
Diffuser	Opal PC
Beam Angle	120°
Color Available	Black & Grey
Lifespan	> 50,000 Hours (L70 B10)
Voltage	AC220~240V
Working Temperature	-20C° ~ +65C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	65
IK	10

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-STR318860	60W	LED	4*1003lm	A1300 X B565 X C1880 mm
LP-STR318890	90W	LED	6*1003lm	A1550 X B675 X C1780 mm
LP-STR3188180	180W	LED	9*1262lm	A2130 X B790 X C1980 mm
LP-STR3188220	220W	LED	11*1262lm	A2130 X B790 X C2215 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 16:31.