

TENDER TEXT



DECORATIVE POLES

York

LP-STR318430



TENDER TEXT

Supply and install York (LP-STR318430) Decorative Pole by LIGHT PLUS UK. Housing: Die Cast Aluminum, Extruded Aluminum Pole. Diffuser: Opal PC. Beam Angle: 113°. Color Available: Black & Grey. Lifespan: > 50,000 Hours (L70 B10). Voltage: AC220~240V. Working Temperature: -20C° ~ +65C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 10. Or equal and approved.

DESCRIPTION

LED street luminaire optimized for low maintenance. The sealed light engine resists contamination, reducing lumen depreciation from dirt. Smart-ready sockets and drivers support future controls without redesign.

TECHNICAL CHARACTERISTICS

Housing	Die Cast Aluminum, Extruded Aluminum Pole
Diffuser	Opal PC
Beam Angle	113°
Color Available	Black & Grey
Lifespan	> 50,000 Hours (L70 B10)
Voltage	AC220~240V
Working Temperature	-20C° ~ +65C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	65

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-STR318430	30W	LED	2596lm	A480 X B480 X C320 mm
LP-STR318445	45W	LED	3370lm	A480 X B480 X C320 mm
LP-STR318460	60W	LED	4888lm	A480 X B480 X C320 mm
LP-STR318480	80W	LED	5044lm	A480 X B480 X C320 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.