

TENDER TEXT



DECORATIVE POLES

Arcade

LP-SL315040



TENDER TEXT

Supply and install Arcade (LP-SL315040) Decorative Pole by LIGHT PLUS UK. Housing: Die-cast Aluminum Body. Diffuser: Tempered clear glass. Beam Angle: 115°. Color Available: Black, Grey. Lifespan: >100,000 Hours (L90 B50). Reflector: Aluminium Reflector. Voltage: AC100~240V. Working Temperature: -40C° ~ 55C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 67. IK: 10. Or equal and approved.

DESCRIPTION

The primary appeal of LED street lighting is energy efficiency compared to conventional street lighting fixture technologies such as high-pressure sodium (HPS) and metal halide (MH). Environmentally friendly alternative to traditional lightning. Resistant to ambient temperatures up to 20°C to +55°C. High Power LEDs. Can be mounted on a pole with 60- or 90-mm diameter. The finish is accessible in the RAL colors requested by client.

TECHNICAL CHARACTERISTICS

Housing	Die-cast Aluminum Body
Diffuser	Tempered clear glass.
Beam Angle	115°
Color Available	Black, Grey
Lifespan	>100,000 Hours (L90 B50)
Reflector	Aluminium Reflector
Voltage	AC100~240V
Working Temperature	-40C° ~ 55C°

LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	67
IK	10

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-SL315040	40W	LED	5600lm	A530 X B733 X C158 mm
LP-SL315050	50W	LED	7000lm	A530 X B733 X C158 mm
LP-SL315060	60W	LED	8400lm	A530 X B733 X C158 mm
LP-SL315070	70W	LED	9800lm	A530 X B733 X C158 mm
LP-SL315080	80W	LED	11200lm	A530 X B733 X C158 mm
LP-SL315090	90W	LED	12600lm	A530 X B733 X C158 mm
LP-SL3150100	100W	LED	14000lm	A530 X B733 X C158 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:14.