

TENDER TEXT



DECORATIVE POLES

Flip

LP-STR315025-H300



TENDER TEXT

Supply and install Flip (LP-STR315025-H300) Decorative Pole by LIGHT PLUS UK. Housing: Die Cast Aluminium with High Corrosion Resistance Powder Coated and Stainless Steel Screws. Diffuser: Thermal-shock Resistant Tempered Glass. Beam Angle: 24° / 36° / 45° / 60°. Color Available: Gray. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: 100~240V. Working Temperature: -02C° ~ 55C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 66. Or equal and approved.

DESCRIPTION

Rectangular shape LED lighting element and with innovative technology and modern design. It offers outstanding light efficiency and integrates itself through the design into historic and modern surroundings with asymmetrical optics. The LED system offers durability and optimal lumen output.

TECHNICAL CHARACTERISTICS

Housing	Die Cast Aluminium with High Corrosion Resistance Powder Coated and Stainless Steel Screws
Diffuser	Thermal-shock Resistant Tempered Glass
Beam Angle	24° / 36° / 45° / 60°
Color Available	Gray
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	100~240V
Working Temperature	-02C° ~ 55C°

LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	66

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-STR315025-H300	25W	LED	3750lm	200 X 100 X 275 mm
LP-STR315050-H300	2*25W	LED	7500lm	200 X 100 X 275 mm
LP-STR315035-H450	35W	LED	5250lm	200 X 100 X 275 mm
LP-STR315070-H450	2*35W	LED	10500lm	200 X 100 X 275 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:21.