

TENDER TEXT



LED DRIVERS

SR-2400RB



TENDER TEXT

Supply and install SR-2400RB LED Driver by LIGHT PLUS UK. Designation: DALI MCU. Power connection: L, N AC mains. Operating voltage: 100-240V AC. Power consumption: 2.3W max. DALI connection: DA+/DA-, max. 300m cable length, DALI power supply output current max 100mA. Perm. Cable cross-section: 0.5...1.5 mm². Ambient temperature: 0...+50 °C. Type of protection: IP 20. Protection class: II. Dimensions: 80x80x53mm. Or equal and approved.

TECHNICAL CHARACTERISTICS

Designation	DALI MCU
Power connection	L, N AC mains
Operating voltage	100-240V AC
Power consumption	2.3W max
DALI connection	DA+/DA-, max. 300m cable length, DALI power supply output current max 100mA.
Perm. Cable cross-section	0.5...1.5 mm ²
Ambient temperature	0...+50 °C
Type of protection	IP 20
Protection class	II
Dimensions	80x80x53mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:20.