


TENDER TEXT



LED DRIVERS

SR-2701S-N



TENDER TEXT

Supply and install SR-2701S-N LED Driver by LIGHT PLUS UK. DALI control input: 1. DALI consumption: 3mA. Number of DALI addresses: 1. Switching voltage AC: 100-240V. Switching voltage DC: Max. 30V. Current: Resistive load: max. 4.3A Capacitive load: max. 1.3A Inductive load: max. 4.3A. Type of contact: 1 normally closed. Output 0/1-10V Current: <10mA. Protection class: II. Dimensions: 80x80x53mm. Or equal and approved.

TECHNICAL CHARACTERISTICS

DALI control input	1
DALI consumption	3mA
Number of DALI addresses	1
Switching voltage AC	100-240V
Switching voltage DC	Max. 30V
Current	Resistive load: max. 4.3A Capacitive load: max. 1.3A Inductive load: max. 4.3A
Type of contact	1 normally closed
Output 0/1-10V Current	<10mA
Protection class	II
Dimensions	80x80x53mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.