

TENDER TEXT



SPOT LIGHTS

SHIRE

LP-SL184309



TENDER TEXT

Supply and install SHIRE (LP-SL184309) Spot Light by LIGHT PLUS UK. Housing: Die Cast Aluminum. Diffuser: Iron Frame. Beam Angle: 15° / 24° / 36°. Color Available: White , Black. Reflector: Aluminum Reflector. Lifespan: >50,000 Hours (L80 B10). Voltage: AC220~240V. Working Temperature: -20C° ~ +60C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 20. Or equal and approved.

DESCRIPTION

This focused lighting solution is crafted from robust die-cast aluminum with a protective, high-quality finish, ensuring long term durability and resistance to typical indoor wear. Designed for recessed ceiling installation, it combines a sleek, discreet aesthetic with powerful, energy-efficient LED illumination, enhancing indoor spaces with both elegance and reliable performance.

TECHNICAL CHARACTERISTICS

Housing	Die Cast Aluminum
Diffuser	Iron Frame
Beam Angle	15° / 24° / 36°
Color Available	White , Black
Reflector	Aluminum Reflector
Lifespan	>50,000 Hours (L80 B10)
Voltage	AC220~240V
Working Temperature	-20C° ~ +60C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

IP Rating

20

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions	Cut Out
LP-SL184309	09W	LED	675lm	A85 X B82 mm	Ø75 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:21.