

TENDER TEXT



SPOT LIGHTS

Pioneer

LP-SL192607



TENDER TEXT

Supply and install Pioneer (LP-SL192607) Spot Light by LIGHT PLUS UK. Housing: Die-Cast Aluminum. Diffuser: PMMA Polycarbonate. Color Available: White. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V - 50/60Hz. Working Temperature: -20°~+40°C. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 40. Beam Angle: 15° / 24° / 36° / 60°. Or equal and approved.

DESCRIPTION

Pioneer LED Spot Light Unique detachable structure with various trims combination Curved edge heat sink provides the utmost heat dissipation High lumen LED COB light source with cut-out size 55mm. Pioneer can be used for Modern Work spaces, Institutions, Small Formal Retail Outlets, Hotels and High End Villa's.

TECHNICAL CHARACTERISTICS

Housing	Die-Cast Aluminum
Diffuser	PMMA Polycarbonate
Color Available	White
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V - 50/60Hz
Working Temperature	-20°~+40°C
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	40

Beam Angle 15° / 24° / 36° / 60°

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-SL192607	07W	LED	840lm	AØ78 X B77mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.