

TENDER TEXT



SPOT LIGHTS

NARVI – II

LP-SL192506



TENDER TEXT

Supply and install NARVI – II (LP-SL192506) Spot Light by LIGHT PLUS UK. Housing: Die-Cast Aluminum. Diffuser: Clear Glass. Color Available: White & Black. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -25°~+65°C. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. UGR: <19. IP Rating: 65. Beam Angle: 15° / 24° / 36°. Or equal and approved.

DESCRIPTION

Narvi II recessed square tilting down light is made of constructed from durable die casting aluminum with high efficiency reflector , without any shadow, accurate angle, high lumen and PC clear diffuser and optical lens. Narvi II light fixture features a CREE COB LED module that maintains uniform intensity. It's an excellent lighting choice for the living room, bedroom, hallway, kitchen, offices etc.

TECHNICAL CHARACTERISTICS

Housing	Die-Cast Aluminum
Diffuser	Clear Glass
Color Available	White & Black
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-25°~+65°C
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
UGR	<19

IP Rating	65
Beam Angle	15° / 24° / 36°

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-SL192506	06W	LED	720lm	A90 X B90 X C90mm
LP-SL192510	10W	LED	1200lm	A90 X B90 X C90mm
LP-SL192515	15W	LED	1800lm	A90 X B90 X C90mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.