

TENDER TEXT



SPOT LIGHTS

Vetta

LP-SL187710



TENDER TEXT

Supply and install Vetta (LP-SL187710) Spot Light by LIGHT PLUS UK. Housing: Luminaire Body of Die-cast Aluminum, White, Powder-coated and Heat Sink Form a Compact Unit. Diffuser: Clear Tempered Glass. Beam Angle: 15° / 24° / 36° / 45°. Color Available: White/Black. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -25C° ~ +45C°. UGR: <13. MACADAM: <3. LUMINOUS EFFICACY (LM/W): 120. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 54. IK: 06. Or equal and approved.

DESCRIPTION

Vetta LED Spotlight is recessed ceiling spotlight, with an essential and complementary shape adopts super slim and compact design, perfectly suitable for the narrow ceiling installation. IP65 rating front cover design, suitable for damp environment. T-shape heat sink greatly increases the radiation area and improves cooling efficiency. The fitting could be adjust from 0-30 degree in horizontal direction, which can expand the illumination area.

TECHNICAL CHARACTERISTICS

Housing	Luminaire Body of Die-cast Aluminum, White, Powder-coated and Heat Sink Form a Compact Unit
Diffuser	Clear Tempered Glass
Beam Angle	15° / 24° / 36° / 45°
Color Available	White/Black
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector

Voltage	AC220~240V
Working Temperature	-25C° ~ +45C°
UGR	<13
MACADAM	<3
LUMINOUS EFFICACY (LM/W)	120
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	54
IK	06

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-SL187710	10W	LED	1200lm	A90 X B86 X C83 mm
LP-SL187712	12W	LED	1440lm	A90 X B86 X C83 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:25.