

TENDER TEXT



DOWN LIGHTS

Cama

LP-DL178215



TENDER TEXT

Supply and install Cama (LP-DL178215) Down Light by LIGHT PLUS UK. Housing: Luminaire Body of die-cast Aluminum & Heat Sink Form a Compact Unit, White Powder-coated. Diffuser: Lens (Reflector Optional). Beam Angle: 24° / 38° / 45° / 60°. Color Available: White. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -10C° ~ 50C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 44. Or equal and approved.

DESCRIPTION

Cama LED Down light is unique traditional deep reflector and COB high power LED chip provides perfect combination of high lighting efficiency, comfortable lighting and humanization design, made by high quality Aluminum profile provides excellent thermal dissipation with great heatsink designed for any ceiling installations. Isolated driver solution both in dimmable and non-dimmable version.

TECHNICAL CHARACTERISTICS

Housing	Luminaire Body of die-cast Aluminum & Heat Sink Form a Compact Unit, White Powder-coated.
Diffuser	Lens (Reflector Optional)
Beam Angle	24° / 38° / 45° / 60°
Color Available	White
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-10C° ~ 50C°

LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	44

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-DL178215	15W	LED	1800lm	A130 x B70 x C105 mm
LP-DL178220	20W	LED	2400lm	A165 x B90 x C155 mm
LP-DL178230	30W	LED	3600lm	A185 x B95 x C165 mm
LP-DL178240	40W	LED	4800lm	A220 x B105 x C200 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:25.