

TENDER TEXT



WALL SURFACE

Elegant

LP-ML2206



TENDER TEXT

Supply and install Elegant (LP-ML2206) Wall Surface by LIGHT PLUS UK. Housing: Stainless Steel Cover, Platted die cast Aluminum. Diffuser: Acrylic Opal Diffuser. Beam Angle: 15° / 24° / 36°. Color Available: Acrylic Diffuser & Stainless Steel Chrome Finish. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -10C° ~ 50C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 54. Or equal and approved.

DESCRIPTION

This can be used over or to the side of mirrors and is very popular in both domestic and commercial spaces. This fitting has stainless steel cover, plated die cast aluminum opal glass to provide soft diffused lighting. Ideal for installation above or by the side of a mirror to provide illuminate to the face when washing, shaving or applying make-up. Although ideal for use in the bathroom but can be used elsewhere if required such as a living space or bedroom made of acrylic diffuser stainless steel, aluminum & acrylic chrome finish. Can be installed vertically or horizontally. It is available in IP 54 & IP 65.

TECHNICAL CHARACTERISTICS

Housing	Stainless Steel Cover, Platted die cast Aluminum
Diffuser	Acrylic Opal Diffuser
Beam Angle	15° / 24° / 36°
Color Available	Acrylic Diffuser & Stainless Steel Chrome Finish
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector

Voltage	AC220~240V
Working Temperature	-10C° ~ 50C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	54

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-ML2206	06W	LED	660lm	A440 X B95 X C50 mm
LP-ML2209	09W	LED	990lm	A440 X B95 X C50 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:25.