

TENDER TEXT



FLOOD & SPIKE LIGHTS

Sharp II

LP-FL307080



TENDER TEXT

Supply and install Sharp II (LP-FL307080) Flood & Spike Light by LIGHT PLUS UK. Housing: Die cast Housing with black powder coat. Diffuser: Tempered Glass. Beam Angle: 15° / 24° / 36° / 45° / 60° / 90° / 120°. Color Available: All RAL Color. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -30C° ~ 60C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 66. IK: 08. Or equal and approved.

DESCRIPTION

Sharp II LED Flood Light is a cost-effective solution, with full range of wattage and optional light distribution, Sharp II is available for multiple applications. Multiple light distributions for different applications even for stadium and billboard. It can also be used as street light with slip fitter mounting accessory.

TECHNICAL CHARACTERISTICS

Housing	Die cast Housing with black powder coat.
Diffuser	Tempered Glass
Beam Angle	15° / 24° / 36° / 45° / 60° / 90° / 120°
Color Available	All RAL Color
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-30C° ~ 60C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

IP Rating	66
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-FL307080	80W	LED	8000lm	A287xB236xC160mm
LP-FL3070100	100W	LED	10000lm	A287xB236xC160mm
LP-FL3070120	120W	LED	12000lm	A287xB236xC160mm
LP-FL3070150	150W	LED	15000lm	A287xB236xC160mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:14.