

TENDER TEXT



FLOOD & SPIKE LIGHTS

Gardena

LP-SKL405010



TENDER TEXT

Supply and install Gardena (LP-SKL405010) Flood & Spike Light by LIGHT PLUS UK. Housing: Body in Aluminum Die-casting. Diffuser: Clear Frosted Glass, Silicon Rubber Gasket. Beam Angle: 15° / 25° / 36°. Color Available: Antique Brass & Black. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC100~240V. Working Temperature: -20C° ~ 55C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 67. IK: 08. Or equal and approved.

DESCRIPTION

Environmentally friendly alternative to traditional lighting Spike light. Greatly Ideal for uplighting, accent Landscape Lighting. Fixture Solid brass adjustable thumb screw, horizontal rotation 360°. Input low voltage: 12V AC/DC, excluding the voltage transformer or connector, 5 Years warranty. Resistant to ambient temperatures up to 60°C.

TECHNICAL CHARACTERISTICS

Housing	Body in Aluminum Die-casting
Diffuser	Clear Frosted Glass, Silicon Rubber Gasket
Beam Angle	15° / 25° / 36°
Color Available	Antique Brass & Black
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC100~240V
Working Temperature	-20C° ~ 55C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

IP Rating	67
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-SKL405010	COB 10W	LED	1200lm	A330 X B148 X C10
LP-SKL405015	COB 15W	LED	1800lm	A330 X B148 X C10

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.