




Aqua is a slim, fully sealed fountain luminaire for 360° fountain-jet lighting, replacing the bulky underwater floodlight. The 316 stainless steel body sits flat around the nozzle, which makes installation and maintenance straightforward. Available in white and coloured light, with RGBW and a choice of drivers.

Description


- Housing** - Stainless Steel 316L
- Diffuser** - PMMA Optical Lens with Tempered Glass
- Beam Angle** - 15° / 30° / 45° / 60°
- Color Available** - 2700K, 6500K, Red, Green, Blue, Yellow, Amber, RGBW
- Lifespan** - >50,000 Hours (L80)
- Voltage** - DC24V
- Driver Options** - On/Off, DALI, Dimmable, Phase Dimming, 1-10V
- Working Temperature** - +20C° - +50C°
- Glow Wire Test** - 850°
- Class** - III
- IP Rating** - 68
- IK** - 09
- Thread** - G1 1/2

Item Code	Power	Lamp	Lumen	Dimensions
LP-UL182010	10W	9 x SMD LED		A182 x 37 mm
LP-UL182018	18W	9 x SMD LED		A182 x 37 mm
LP-UL182027	27W	9 x SMD LED		A182 x 37 mm
LP-UL182036	36W	9 x SMD LED		A182 x 37 mm
LP-UL182124	24W	12 x SMD LED		A182 x 37 mm
LP-UL182136	36W	12 x SMD LED		A182 x 37 mm

Photometrics



Technical Drawing




OUTDOOR LIGHTS **AQUA** UNDERWATER LIGHT

Kelvin

- 2700K - warm white, similar to incandescent bulb
- 3000K - soft white, similar to halogen bulb
- 4000K - bright white, similar to fluorescent lighting
- 5000K - daylight, very bright & similar to sunlight
- 6000K - cool white, blue tinted, like a monitor

Beam Angle



LED CHIP



LED DRIVER



A++ ENERGY LEVEL **LED** **SERIES WIRING**



Specifications, materials and finishes may be updated without prior notice as part of our continuous product improvement. Dimensions are nominal. Photometric data is provided for guidance; project-specific calculations should use the current files available on request. The latest version of this datasheet is published at www.lightplus.uk and takes precedence over any printed copy.



www.lightplus.uk