

TENDER TEXT



BOLLARDS

Dorset

LP-BL335903



TENDER TEXT

Supply and install Dorset (LP-BL335903) Bollard by LIGHT PLUS UK. Housing: Die-Cast Aluminum and Extruded Aluminum Pole. Diffuser: Clear Glass. Beam Angle: 60°. Color Available: Black & Grey. Lifespan: >50,000 Hours (L90 B10). Voltage: AC220~240V. Working Temperature: -20°C~+65°C. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 09. Or equal and approved.

DESCRIPTION

An LED bollard designed for pathways and landscaped zones. A die-cast aluminum body with a durable powder coat resists corrosion, while the sealed optical chamber provides uniform, low-glare light. Comes with wide or symmetrical distributions and multiple height options. IP65 and IK10 ratings support harsh outdoor use, with concealed fixings and a pre-wired base for quick, tidy installation.

TECHNICAL CHARACTERISTICS

Housing	Die-Cast Aluminum and Extruded Aluminum Pole
Diffuser	Clear Glass
Beam Angle	60°
Color Available	Black & Grey
Lifespan	>50,000 Hours (L90 B10)
Voltage	AC220~240V
Working Temperature	-20°C~+65°C
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	65

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-BL335903	03W	LED	384lm	AØ130 X B400 mm
LP-BL335906	06W	LED	507lm	AØ130 X B650 mm
LP-BL335910	10W	LED	917lm	AØ130 X B800 mm
LP-BL335915	03W	LED	1191lm	AØ130 X B800 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:25.