



OUTDOOR LIGHTS LEICESTER

BOLLARD LIGHT

Kelvin

- 2700K – warm white, similar to incandescent bulb
- 3000K – soft white, similar to halogen bulb
- 4000K – bright white, similar to fluorescent lighting
- 5000K – daylight, very bright & similar to sunlight
- 6000K – cool white, blue tinted, like a monitor

Beam Angle



A clean cylindrical LED bollard that complements modern landscaping. The powder-coated aluminum enclosure resists UV fade and corrosion. Clear, prismatic, or opal optics deliver uniform light with minimal glare. Serviceable gear tray and stainless-steel fasteners make maintenance straight forward.

LED CHIP



LED DRIVER




Description


- Housing** - Die-Cast Aluminum and Extruded Aluminum Pole
- Diffuser** - Tempered Clear Glass
- Color Available** - Black & Grey
- Lifespan** - >50,000 Hours (L90 B10)
- Voltage** - AC220~240V
- Working Temperature** - -20C° ~ +65C°
- IP Rating** - 65
- IK** - 09

Item Code	Power	Lamp	Lumen	Dimensions
LP-BL335210	10W	LED	562lm	A120 X B370 mm A120 X B650 mm A120 X B1000 mm
LP-BL335215	15W	LED	843lm	A120 X B370 mm A120 X B650 mm A120 X B1000 mm

Photometrics



Technical Drawing



WALL VERSION



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk