

TENDER TEXT



BOLLARDS

Thames

LP-BL334506



TENDER TEXT

Supply and install Thames (LP-BL334506) Bollard by LIGHT PLUS UK. Housing: Die-Cast Aluminum and Extruded Aluminum Pole. Diffuser: Frosted Glass. Beam Angle: 53°. Color Available: Black & Grey. Lifespan: >50,000 Hours (L90 B10). Voltage: AC220~240V. Working Temperature: -20°C~+65°C. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 54. IK: 09. Or equal and approved.

DESCRIPTION

This LED bollard delivers comfortable pathway lighting with restrained glare and clean cut-off. The sealed optic and weather-rated gaskets keep moisture and dust out. Offered with symmetric or forward-throw distributions to keep light where it is needed. Root or surface mounting options simplify installation on new builds or refurbishment.

TECHNICAL CHARACTERISTICS

Housing	Die-Cast Aluminum and Extruded Aluminum Pole
Diffuser	Frosted Glass
Beam Angle	53°
Color Available	Black & Grey
Lifespan	>50,000 Hours (L90 B10)
Voltage	AC220~240V
Working Temperature	-20°C~+65°C
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	54

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-BL334506	06W	LED	170lm	A120 X B80 X C400 mm A120 X B80 X C650 mm A120 X B80 X C800 mm
LP-BL334510	10W	LED	170lm	A120 X B80 X C400 mm A120 X B80 X C650 mm A120 X B80 X C800 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:14.