

TENDER TEXT



BOLLARDS

Liny

LP-BL337008-H80



TENDER TEXT

Supply and install Liny (LP-BL337008-H80) Bollard by LIGHT PLUS UK. Housing: Body is Die-casting Aluminum Cover, Extruded Aluminum Pole. Finishing Surface Anti-ageing Electrostatic Spray Processing. Diffuser: PMMA. Beam Angle: 15° / 36°. Color Available: White & Black. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: 100~240V. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 08. Or equal and approved.

DESCRIPTION

The Liny LED bollard lighting adopts high-quality aluminum shell, spray paint baking surface treatment technology, and has the characteristics of not easy to rust, waterproof and sunscreen. The color of the lamp body, the light source and the power of the light source can be selected independently, which can match most scenes and spaces well, bringing good light effect and visual effect.

TECHNICAL CHARACTERISTICS

Housing	Body is Die-casting Aluminum Cover, Extruded Aluminum Pole. Finishing Surface Anti-ageing Electrostatic Spray Processing
Diffuser	PMMA
Beam Angle	15° / 36°
Color Available	White & Black
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	100~240V
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

IP Rating	65
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-BL337008-H80	08W	LED	960lm	A40 X B800 mm
LP-BL337008-H60	08W	LED	960lm	A40 X B800 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:25.