

TENDER TEXT



SOLAR LIGHTS

Mara

LP-SLR8010



TENDER TEXT

Supply and install Mara (LP-SLR8010) Solar Light by LIGHT PLUS UK. Housing: Aluminum Alloy. Diffuser: Polycarbonate. Beam Angle: 15° / 24° / 36°. Color Available: Grey. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Working Temperature: -20C° ~ 65C°. Cell Type: Aluminium Alloy. Battery: Lithium (LiFePO4). Charge Time: 10 Hours. Discharge Time: 2 Rainy Days. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 10. Or equal and approved.

DESCRIPTION

Mara solar wall light is royal quality with ultra high lumens output. It is a integration with mono solar panel, and 3.2V 12AH battery pack and high efficiency LEDs source. This solar motion sensor light have 3 working modes with three color indicator lights. The updated bigger solar panel can quickly absorb sun rays and generate electricity for light. The all-in-one design simple LED wall lights offer a fresh feel to your contemporary outdoor decor. And perhaps best of all, this romantic ambiance is achieved with an eco friendly and low-maintenance effect.

TECHNICAL CHARACTERISTICS

Housing	Aluminum Alloy
Diffuser	Polycarbonate
Beam Angle	15° / 24° / 36°
Color Available	Grey
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Working Temperature	-20C° ~ 65C°

Cell Type	Aluminium Alloy
Battery	Lithium (LiFePO4)
Charge Time	10 Hours
Discharge Time	2 Rainy Days
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	65
IK	10

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-SLR8010	10W	LED	1000lm	A118 X B365 X C205 mm
LP-SLR8015	15W	LED	1500lm	A118 X B365 X C205 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:25.