

TENDER TEXT



SURFACE PROFILE

LP-Pro

LP-SRL28



TENDER TEXT

Supply and install LP-Pro (LP-SRL28) Surface Profile by LIGHT PLUS UK. Housing: Anodized Aluminum. Diffuser: Polycarbonate Cover. Color Available: White. Lifespan: >50,000 Hours (L80 B10). Reflector: Aluminium Reflector. Voltage: 24V DC. Working Temperature: -20C° ~ +50C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 44. IK: 08. Or equal and approved.

DESCRIPTION

A modern sleek design aluminum LED profile for recessed mounted, excellent solution for indoor/outdoor lighting or decorative applications.

TECHNICAL CHARACTERISTICS

Housing	Anodized Aluminum
Diffuser	Polycarbonate Cover
Color Available	White
Lifespan	>50,000 Hours (L80 B10)
Reflector	Aluminium Reflector
Voltage	24V DC
Working Temperature	-20C° ~ +50C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	44
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-SRL28	28W/M	LED	2800lm/M	A50 X B35 X C65 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:25.