




Kelvin

2700K – warm white, similar to incandescent bulb
3000K – soft white, similar to halogen bulb
4000K – bright white, similar to fluorescent lighting
5000K – daylight, very bright & similar to sunlight
6000K – cool white, blue tinted, like a monitor
TRIO CCT – Three selectable color temperatures.

Beam Angle



This focused lighting solution is crafted from robust die-cast aluminum with a protective, high-quality finish, ensuring long term durability and resistance to typical indoor wear. Designed for recessed ceiling installation, it combines a sleek, discreet aesthetic with powerful, energy-efficient LED illumination, enhancing indoor spaces with both elegance and reliable performance.

LED CHIP



LED DRIVER




Description

Housing - Die Cast Aluminum
Diffuser - PMMA Opal PC Lens
Reflector - Mirror Finished Aluminum Reflector
Color Available - White, Black
Lifespan - >50,000 Hours (L80 B10)
Voltage - AC220~240V
Working Temperature - -20C° ~ +60C°
IP Rating - 20


Item Code	Power	Lamp	Lumen	Dimensions	Cut Out
LP-SL172307	07W	LED	840lm	A62 X B78 mm	Ø55 mm
LP-SL172310	10W	LED	1200lm	A72 X B78 mm	Ø65 mm
LP-SL172315	15W	LED	1800lm	A82 X B78 mm	Ø75 mm



Photometrics



Technical Drawing



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk