



Bulk, a great looking outdoor light fitting, excellent for lighting your building, Ideal for use along walkways, pavements or either side of a doorway and with its opal diffuser, this fitting is perfect installed at any height without risk of glare. Versatile in nature this fitting is ideal for use on with the wall or ceiling with impact-resistant synthetic covers made of polycarbonate. Available in a choice of three fabulous colour finishes, white, Black, or silver grey.

Description

Housing - Die-cast Aluminum

Diffuser - 94-v0 Fire-rated PC diffuser

Reflector - Aluminium Reflector

Color Available - White, Black & Dark-Gray

Lifespan - >50,000 Hours (L90 B10)

Voltage - AC220~240V


Working Temperature - -10C° ~ +50C°

IP Rating - 65


IK - 10

Item Code	Power	Lamp	Lumen	Dimensions
LP-ODL349012	12W	LED	1440lm	A275 X B70mm
LP-ODL349024	24W	LED	2880lm	A275 X B70mm

Photometrics



Technical Drawing



OUTDOOR LIGHTS BULK

WALL SURFACE LIGHT

Kelvin

2700K - warm white, similar to incandescent bulb

3000K - soft white, similar to halogen bulb

4000K - bright white, similar to fluorescent lighting

5000K - daylight, very bright & similar to sunlight

6000K - cool white, blue tinted, like a monitor

Beam Angle



LED CHIP



LED DRIVER



TRIDONIC

PHILIPS



LED



SERIES
WIRING



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk