




OUTDOOR LIGHTS CALLISTA

DECORATIVE POLE

Kelvin

- 2700K – warm white, similar to incandescent bulb
- 3000K – soft white, similar to halogen bulb
- 4000K – bright white, similar to fluorescent lighting
- 5000K – daylight, very bright & similar to sunlight
- 6000K – cool white, blue tinted, like a monitor

Beam Angle



LED CHIP



LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk




The Callista meets the need for scenic and flexible, as well as discreet, larger scale illumination in a range of applications from public parks, urban squares, city centres and ocean fronts. The aesthetic design has the same subtle sculptural appearance, complementing both modern and classic urban spaces. Callista is high quality LED Chips. Driver with 0-10V/DALI/Programmed options, and with surge protections up to 20KV. Based on the same design language and basic idea, one single asymmetric carving opens up for the light. The distinctive carving gives the luminaire character, while also serving as a dimming reflector, softening the light and making it more pleasant in the dark of night, while also directing it precisely where needed.

Description

- Housing** - Die Cast Cover and Extruded Aluminum
- Diffuser** - Tempered Glass Diffuser
- Color Available** - Black, Gray, Any RAL Color
- Lifespan** - >100,000 Hours (L90 B10)
- Voltage** - AC100~240V
- IP Rating** - 66
- IK** - 08

Item Code	Power	Lamp	Lumen	Dimensions
LP-GDL318018-120	1X20W	LED	2400lm	A168 X B2000mm
LP-GDL318018-220	2X20W	LED	4800lm	A168 X B2700mm
LP-GDL318018-320	3X20W	LED	7200lm	A168 X B3500mm
LP-GDL318018-420	4X20W	LED	9600lm	A168 X B4500mm

Photometrics



Technical Drawing

