



Cambridge LED Street light for hot climates and coastal areas. A marine-grade coating is available for enhanced corrosion resistance. The thermal path is engineered to protect the LEDs and driver under continuous operation.

Description

Housing - Stainless Steel and Aluminum Body

Diffuser - Clear Glass

Color Available - Black & Grey

Lifespan - >50,000 Hours (L70 B10)

Voltage - AC220-240V


Working Temperature - -20° ~ +65°C

IP Rating - 65

IK - 10

Item Code	Power	Lamp	Lumen	Dimensions
LP-STR319640	40W	LED	-----	AØ750 X B382 mm

Technical Drawing



OUTDOOR LIGHTS CAMBRIDGE

DECORATIVE POLE

Kelvin

2700K - warm white, similar to incandescent bulb

3000K - soft white, similar to halogen bulb

4000K - bright white, similar to fluorescent lighting

5000K - daylight, very bright & similar to sunlight

6000K - cool white, blue tinted, like a monitor

Beam Angle



LED CHIP



LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk