



Kelvin

2700K – warm white, similar to incandescent bulb

3000K – soft white, similar to halogen bulb

4000K – bright white, similar to fluorescent lighting

5000K – daylight, very bright & similar to sunlight

6000K – cool white, blue tinted, like a monitor

Beam Angle



LED CHIP



LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk

Description

Housing - Die-cast Aluminum

Diffuser - Clear and Frosted Diffuser

Reflector - Aluminium Reflector

Color Available - Black & Gray

Lifespan - >50,000 Hours (L90 B10)

Voltage - AC220~240V


Working Temperature - -30C° ~ +55C°

IP Rating - 65

IK - 10

Item Code	Power	Lamp	Lumen	Dimensions
LP-ODL373609	09W	LED	1080lm	A280 X B185 X C80mm
LP-ODL373612	12W	LED	1440lm	A280 X B185 X C80mm
LP-ODL373615	15W	LED	1800lm	A280 X B185 X C80mm

Photometrics



Technical Drawing

