



OUTDOOR LIGHTS CLOVELLY

BOLLARD LIGHT

Kelvin

- 2700K – warm white, similar to incandescent bulb
- 3000K – soft white, similar to halogen bulb
- 4000K – bright white, similar to fluorescent lighting
- 5000K – daylight, very bright & similar to sunlight
- 6000K – cool white, blue tinted, like a monitor

Beam Angle



A versatile LED bollard with a restrained form factor. The light engine offers high efficacy and long service life with integral driver. Choose from forward-throw or symmetrical light patterns to optimize spacing. Hardware is stainless steel, and finishes are offered in standard architectural colors.

LED CHIP



LED DRIVER




Description

- Housing** - Die-Cast Aluminum and Extruded Aluminum Pole
- Diffuser** - Clear Glass
- Color Available** - Black & Grey
- Lifespan** - >50,000 Hours (L90 B10)
- Voltage** - AC220~240V
- Working Temperature** - -20C° ~ +65C°
- IP Rating** - 65
- IK** - 09


Item Code	Power	Lamp	Lumen	Dimensions
LP-BL335810	10W	LED	197lm	A120 X B80 X C230 mm A120 X B80 X C400 mm A120 X B80 X C650 mm A120 X B80 X C800 mm



Photometrics



Technical Drawing



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk