



Indoor and outdoor ceiling light fixture suitable for homes, shops, offices production sites.

Description

Housing - Injection moulded thermo polycarbonate (PMMA) material reinforced with fiber glass.

Diffuser - Opal injection moulded polycarbonate diffuser

Reflector - High purity anodized aluminum reflector

Color Available - White, Black and Grey


IP Rating - 44

Standards - Designed and Manufactured to comply with EN 60598

Item Code	Power	Lamp	Lumen	Dimensions
LP-553118	18W	LED	840lm	120x32mm
LP-553132	26/36W	LED	1440lm	170x32mm
LP-554218	2X18W	LED	2400lm	255x32mm
LP-554226	2X26W	LED	1440lm	170x32mm

Photometrics

Technical Drawing



OUTDOOR LIGHTS DOOMY

WALL SURFACE LIGHT

Kelvin

2700K - warm white, similar to incandescent bulb


3000K - soft white, similar to halogen bulb

4000K - bright white, similar to fluorescent lighting

5000K - daylight, very bright & similar to sunlight

6000K - cool white, blue tinted, like a monitor

Beam Angle



LED CHIP



LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk