



OUTDOOR LIGHTS EMBER

WALL RECESSED LIGHT

Kelvin

- 2700K – warm white, similar to incandescent bulb
- 3000K – soft white, similar to halogen bulb
- 4000K – bright white, similar to fluorescent lighting
- 5000K – daylight, very bright & similar to sunlight
- 6000K – cool white, blue tinted, like a monitor

Beam Angle



A recessed wall light is a small luminaire designed to be installed surface mounted. Its high-quality raw material ensures high resistance to dust, humidity and water. High efficiency LED lights provide more luminous and brighter with low consumption. This product has features as easy installation and low maintenance requirements. It enhances overall brightness and creates mood lighting. It is suitable for application as public, residential or pedestrian areas, parks, gardens and shopping malls.

Description

- Housing** - Powder Coated Die-Casting Aluminum
- Diffuser** - Polycarbonate Optical Lens
- Color Available** - Choice of RAL Colors
- Lifespan** - >50,000 Hours (L80 B10 F10)
- Voltage** - AC85-265V
- Working Temperature** - -30C° ~ +50C°
- IP Rating** - 66
- IK** - 08

Item Code	Power	Lamp	Lumen	Dimensions
LP-STL275101	01W	LED	120lm	A80 X B48 X C80 mm
LP-STL275103	03W	LED	360lm	A80 X B48 X C80 mm

LED CHIP



LED DRIVER




This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk

Photometrics



Technical Drawing

