




This pendant offers another option for contemporary indoor lighting solutions. Indoor suspended linear fitting with integrated LED sources and direct light emission structure, with durable white, black powder coat finish, PMMA diffuser, offering a comfortable diffused light, High transmission opal diffuser, Suspension installation.

Description


- Housing** - Die cast aluminum
- Diffuser** - Satinised PMMA cover
- Color Available** - White & Black
- Lifespan** - L80/B10/F10 50,000 hrs
- Voltage** - 85-265V 50/60Hz
- Working Temperature** - -30C° ~ +65C°
- IP Rating** - IP44

Item Code	Power	Lamp	Lumen	Dimensions
LP-PL258020	20W	LED	2800lm	A500 X B12mm H
LP-PL258035	35W	LED	4900lm	A500 X B12mm H

Photometrics



Technical Drawing




INDOOR LIGHTS GHALA

PENDANT LIGHT

Kelvin

- 2700K - warm white, similar to incandescent bulb
- 3000K - soft white, similar to halogen bulb
- 4000K - bright white, similar to fluorescent lighting
- 5000K - daylight, very bright & similar to sunlight
- 6000K - cool white, blue tinted, like a monitor

Beam Angle



LED CHIP



LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk