



An attractive post top lantern for residential areas, parks and amenity areas. Die-cast aluminum body with powder coating finished. Vandal resistant V2 self-extinguishing, UV-stabilized polycarbonate diffuser. Internal Aluminum reflector option enhances downward light to increase efficiency and save energy. 60mm post top mounting. A smart and affordable choice with low energy consumption. Long-lasting performance in tough environment. Up to 40% in energy saving. Versatile and meets multiple requirements. Application: Landscape, Station Area, Exhibition Area, Shopping Plaza, Car Park, Factories, Public spaces, Parks.

Description

- Housing** - Die-casting Aluminum
- Diffuser** - Polycarbonate
- Reflector** - Aluminum Reflector
- Color Available** - Black, Dark-Gray
- Lifespan** - >50,000 Hours (L90 B10)
- Voltage** - AC220~240V
- IP Rating** - 65
- IK** - 08

Item Code	Power	Lamp	Lumen	Dimensions
LP-GDL3136LED	36W	LED	ADJUST	A600 X B430 X C76mm


OUTDOOR LIGHTS GLORY II

DECORATIVE POLE

Kelvin

- 2700K - warm white, similar to incandescent bulb
- 3000K - soft white, similar to halogen bulb
- 4000K - bright white, similar to fluorescent lighting
- 5000K - daylight, very bright & similar to sunlight
- 6000K - cool white, blue tinted, like a monitor

Beam Angle



LED CHIP



LED DRIVER




This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk

Photometrics



Technical Drawing

