




Kelvin

- 2700K – warm white, similar to incandescent bulb
- 3000K – soft white, similar to halogen bulb
- 4000K – bright white, similar to fluorescent lighting
- 5000K – daylight, very bright & similar to sunlight
- 6000K – cool white, blue tinted, like a monitor

Beam Angle



LED CHIP



LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk




This pendant offers another option for contemporary indoor lighting solutions. Its triangle-like body shape adds vitality to the integrated environment, Premium aluminum housing, anodized or color powder coating. Suspension installation.

Description

- Housing** - Premium Aluminum Housing, Anodized or Color Powder Coating
- Diffuser** - High Transmission Opal Diffuser
- Reflector** - Aluminium Reflector
- Color Available** - White, Dark-Grey, Black
- Lifespan** - >50,000 Hours (L80 B10)
- Voltage** - AC200~240V
- Working Temperature** - -30C° ~ +65C°
- IP Rating** - 54
- IK** - 08

Item Code	Power	Lamp	Lumen	Dimensions
LP-PL231036	36W	LED	3600lm	A1198xB142xC130mm
LP-PL231040	40W	LED	4000lm	A1198xB142xC130mm
LP-PL232045	45W	LED	4500lm	A1198xB142xC130mm

Photometrics



Technical Drawing

