



Kelvin

2700K – warm white, similar to incandescent bulb

3000K – soft white, similar to halogen bulb

4000K – bright white, similar to fluorescent lighting

5000K – daylight, very bright & similar to sunlight

6000K – cool white, blue tinted, like a monitor

Beam Angle



LED CHIP



LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk

Description

Housing - Body is Die-casting Aluminum Cover, Extruded Aluminum Pole. Finishing Surface Anti-ageing Electrostatic Spray Processing.

Diffuser - PMMA

Reflector - Aluminum Reflector

Color Available - White & Black

Lifespan - >50,000 Hours (L90 B10)


Voltage - AC100~240V

IP Rating - 66

IK - 08

Item Code	Power	Lamp	Lumen	Dimensions
LP-BL335015-H100	15W	LED	1800lm	A40 X B800mm
LP-BL335025-H100	25W	LED	3000lm	A40 X B600mm
LP-BL335035-H100	35W	LED	4200lm	A40 X B800mm

Photometrics



Technical Drawing

