



OUTDOOR LIGHTS LUTON

BOLLARD LIGHT

Kelvin

- 2700K – warm white, similar to incandescent bulb
- 3000K – soft white, similar to halogen bulb
- 4000K – bright white, similar to fluorescent lighting
- 5000K – daylight, very bright & similar to sunlight
- 6000K – cool white, blue tinted, like a monitor

Beam Angle



LED CHIP



LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk

Description

Housing - Die-Cast Aluminum and Extruded Aluminum Pole

Diffuser - Opal PC

Color Available - Black & Grey

Lifespan - >50,000 Hours (L90 B10)

Voltage - AC220~240V


Working Temperature - -20C° ~ +65C°

IP Rating - 65

IK - 09

Item Code	Power	Lamp	Lumen	Dimensions
LP-BL336208	08W	LED	E27	A120 X B120 X C400 mm
				A120 X B120 X C650 mm
				A120 X B120 X C800 mm
LP-BL336260	60W	LED	E27	A120 X B120 X C400 mm
				A120 X B120 X C650 mm
				A120 X B120 X C800 mm

Photometrics



Technical Drawing

