



INDOOR LIGHTS LUXY II

PANEL LIGHT

Kelvin

- 2700K – warm white, similar to incandescent bulb
- 3000K – soft white, similar to halogen bulb
- 4000K – bright white, similar to fluorescent lighting
- 5000K – daylight, very bright & similar to sunlight
- 6000K – cool white, blue tinted, like a monitor

Beam Angle



Luxy LED panel adopts high lumen SMD LED with up to 80% energy saving compared to standard CFL. Long a lifetime of 50,000 hours. The top branded driver comes with Triac dim, 0-10V dim, and DALI dim, it has a perfect dimming range and shares great compatibility with worldwide famous brand dimmers. 120° wide beam angle.

The ultra-slim profile fits seamlessly into any workplace. It is available in various installation ways: embedded into the ceiling, suspended with hanging wires, surface mounted in a concrete ceiling by using a surface mounting frame.

Description

Housing - Sheet Steel of Aluminum
Diffuser - PMMA Polycarbonate Lens
Reflector - Aluminium Reflector

Color Available - White

Lifespan - >50,000 Hours (L80 B10)

Voltage - AC220~240V

Working Temperature - -20C° ~ +50C°

IP Rating - 44, 54

IK - 08

LED CHIP



LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.


If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk

Item Code	Power	Lamp	Lumen	Dimensions
LP-7032-SMT-36	36W	LED	4320lm	A595 x B595 x C29mm
LP-7032-SMT-40	40W	LED	4800lm	A595 x B595 x C29mm
LP-7032-SMT-45	45W	LED	5400lm	A595 x B595 x C29mm
LP-7032-SMT-50	50W	LED	6000lm	A595 x B595 x C29mm
LP-7032-SMT-60	60W	LED	7200lm	A595 x B595 x C29mm

Photometrics



Technical Drawing

