



OUTDOOR LIGHTS OXFORD

BOLLARD LIGHT

Kelvin

2700K – warm white, similar to incandescent bulb
 3000K – soft white, similar to halogen bulb
 4000K – bright white, similar to fluorescent lighting
 5000K – daylight, very bright & similar to sunlight
 6000K – cool white, blue tinted, like a monitor

Beam Angle



A Oxford LED bollard for pedestrian routes, courtyards, and hotel gardens. The housing is die-cast aluminum with UV-stable powder coating, and the impact-resistant lens protects the optics. Choose opal or clear lenses with optional louvres for comfort. Integral control gear, surge protection, and stainless hardware ensure reliable, low-maintenance operation.

LED CHIP



LED DRIVER




Description


Housing - Die-Cast Aluminum and Extruded Aluminum Pole
Diffuser - Clear PC
Color Available - Black & Grey
Lifespan - >50,000 Hours (L90 B10)
Voltage - AC220~240V
Working Temperature - -20C° ~ +65C°
IP Rating - 54
IK - 09

Item Code	Power	Lamp	Lumen	Dimensions
LP-BL334206	06W	LED	268lm	A80 X B120 X C400 mm A80 X B120 X C650 mm A80 X B120 X C800 mm
LP-BL33422X6	2x6W	LED	268lm	A80 X B120 X C400 mm A80 X B120 X C650 mm A80 X B120 X C800 mm

Photometrics



Technical Drawing



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk