



Kelvin

2700K – warm white, similar to incandescent bulb

3000K – soft white, similar to halogen bulb

4000K – bright white, similar to fluorescent lighting

5000K – daylight, very bright & similar to sunlight

6500K – cool white, blue tinted, like a monitor

Beam Angle



LED CHIP



LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk

Description

Housing - Luminaire Body of Die-Cast Aluminum, White Powder-Coated

Diffuser - Opal or Frosted PMMA / PC Diffuser

Color Available - White, Black

Lifespan - >50,000 Hours (L90 B10)


Voltage - AC220~240V

Working Temperature - -20C° ~ +55C°

IP Rating - 54

Item Code	Power	Lamp	Lumen	Dimensions
LP-SL182912	12W	LED	1440lm	A86 X B75 X C41 mm
LP-SL182918	18W	LED	2160lm	A110 X B95 X C41 mm
LP-SL182924	24W	LED	2880lm	A135 X B115 X C65 mm

Photometrics



Technical Drawing

