




INDOOR LIGHTS ROUNDY

PENDANT LIGHT

Kelvin

- 2700K – warm white, similar to incandescent bulb
- 3000K – soft white, similar to halogen bulb
- 4000K – bright white, similar to fluorescent lighting
- 5000K – daylight, very bright & similar to sunlight
- 6000K – cool white, blue tinted, like a monitor

Beam Angle



This pendant offers another option for contemporary indoor lighting solutions. Surrounded by a cylindrical metal structure, with durable white/silver/black powder coat finish, PMMA diffuser, offering a comfortable diffused light, High transmission opal diffuser, Suspension installation

LED CHIP



LED DRIVER




Description


- Housing** - Metal Powder Coated Finish
- Diffuser** - PMMA
- Reflector** - Aluminium Reflector
- Color Available** - White, Dark-Grey, Black
- Lifespan** - >50,000 Hours (L80 B10)
- Voltage** - AC200~240V
- Working Temperature** - -30C° ~ +65C°
- IP Rating** - 54
- IK** - 08

Item Code	Power	Lamp	Lumen	Dimensions
LP-PL232025	25W	LED	3000lm	A360 X B90mm
LP-PL232030	30W	LED	3600lm	A480 X B90mm
LP-PL232036	36W	LED	4320lm	A600 X B90mm
LP-PL232040	40W	LED	4800lm	A600 X B90mm

Photometrics



Technical Drawing



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk