




OUTDOOR LIGHTS SIDY II

WALL SURFACE LIGHT

Kelvin

- 2700K – warm white, similar to incandescent bulb
- 3000K – soft white, similar to halogen bulb
- 4000K – bright white, similar to fluorescent lighting
- 5000K – daylight, very bright & similar to sunlight
- 6000K – cool white, blue tinted, like a monitor

Beam Angle



Sidy-II, the high efficient LED system provides excellent result in luminous flux, light brightness, light uniformity and light pleasantness. Available in -up or up-and down light option. Sidy-II LED wall light looks fabulous at the entrance to any modern home, with its light that can optionally be used either side of a door way for a beautiful framing etc.

LED CHIP



LED DRIVER




Description

- Housing** - Die-cast Aluminum
- Diffuser** - 94-v0 Fire-rated PC Diffuser
- Reflector** - Aluminium Reflector
- Color Available** - Black, White
- Lifespan** - >50,000 Hours (L90 B10)
- Voltage** - AC220~240V
- Working Temperature** - -30C° ~ +45C°
- IP Rating** - 66
- IK** - 10


Item Code	Power	Lamp	Lumen	Dimensions
LP-ODL372506	2X6W	LED	1440lm	A60 X B155 X C118mm
LP-ODL372512	2X12W	LED	2880lm	A108 X B258 X C167mm
LP-ODL372515	2X15W	LED	3600lm	A108 X B258 X C167mm



Photometrics



Technical Drawing



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk