



Spoter LED Spot Light has a strong light without glare, it is a perfect choice for functional observer for high-end residential or hospitality settings. This versatile, elegant architectural spot light will bring pure form, definition and quality light to any space without stealing all the attention. Attractive exclusive spot light for indoor or outdoor use, particularly well suited to basic lighting due to its very low unified glare rating. Well integrated LED chip and associated dimmable driver. Made of die-cast powder-coated aluminium.

Description

Housing - Die-casting Aluminum. with White Powder Spraying On The Surface

Diffuser - Glass Diffuser

Reflector - Aluminum Reflector

Color Available - White

Lifespan - >50,000 Hours (L90 B10)


Voltage - AC220~240V

Working Temperature - -10C° ~ +50C°


UGR - <19

Item Code	Power	Lamp	Lumen	Dimensions
LP-SL 189235	35W	LED	3150lm	A190XB 130XC90mm
LP-SL 189245	45W	LED	4050lm	A190XB 130XC90mm

Photometrics



Technical Drawing



INDOOR LIGHTS SPOTER

DOWN LIGHT

Kelvin

2700K - warm white, similar to incandescent bulb


3000K - soft white, similar to halogen bulb

4000K - bright white, similar to fluorescent lighting

5000K - daylight, very bright & similar to sunlight

6500K - cool white, blue tinted, like a monitor

Beam Angle



LED CHIP



LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk